



Dynamic Solutions
INTERNATIONAL

"Protecting the World's Information"



DSI520 Enterprise Series

Experience You Can Trust

Protecting the world's information is our mission. Offering 45+ years of experience in data protection solutions and expertise in both disk and tape technologies, DSI meets the needs of IT professionals worldwide. DSI offers optimized solutions for data backup, recovery and archiving. DSI has award winning designs, patented technologies, superior reliability, first class service and a variety of solutions customized to meet your needs.

Maximize Use of Valuable Resources

The DSI520 Series Virtual Tape Library offers the most robust data protection for our customers. The DSI520-EV0 may be paired with any DSI qualified fibre-channel external storage in your environment, or the DSI520 series expansion modules, allowing expansion into the petabytes of backup capacity.

Protect Your Investment

Data security is imperative when building a backup and disaster recovery solution. DSI utilizes the industry's top standards for at-rest and in-flight encryption to ensure that your data is never exposed to outside threats. The DSI520 ships standard with in-flight and at-rest encryption so your data is protected every step of the way.

Maximize Your Data Center Efficiency

Data centers worldwide face the challenge of business critical data growing exponentially. The DSI520 Enterprise Series may be paired with deduplicating systems to insure maximum possible power, management and physical space efficiency. DSI also offers consulting services to assist with strategic backup and disaster recovery (DR) planning, design and implementation.

Cloud Export

The DSI540 Series now offers the ability to export and recover tape data directly to/from cloud object storage, from Microsoft Azure or Amazon Web Services (S3).

Component Description for DSI520

DSI520-EV0: may be paired with any DSI qualified Fibre-Channel external storage in your environment, or the DSI520 Series expansion modules, allowing expansion into the petabytes of backup capacity.

DSI520-EVD: The enterprise deduplication module may be paired with either DSI's expansion modules or certified third-party disk arrays. No physical storage is included with the EVD head node.



See configuration table for details.

THE **DSI520** IS
DESIGNED TO HELP
YOU KEEP PACE
WITH YOUR
RAPIDLY
EXPANDING DATA
FOOTPRINT BY
UTILIZING STATE-
OF-THE-ART
DEDUPLICATION.

UNISYS

Dynamic Solutions International
373 Inverness Parkway
Suite 110
Englewood, CO 80112

Phone 303.754.2088
Fax 303.754.2066
DynamicSolutions.com

	 DSI520-EV0	 DSI520-EVD
	VTL Node	Deduplication Node
End user capacity	Up to 3.8PB	
	Enterprise VTL Node	Enterprise Deduplication Node
# virtual libraries	128	
# virtual tape drives	1,024	
# virtual tape cartridges supported	250,000	
Backend physical tape	FC only	
Replication (w/ encryption / compression)	Optional	
SecureTape encryption	Optional	
Tape consolidation (stacking)	Optional	
High Availability	Optional	N + 1 Option
Data De-duplication	Requires DSI520 EVD	Yes
VTL Agent	Optional	N/A
Open systems ISV attachment	Yes	Yes
DSI TapeManager / LibraryManager	Optional	N/A
Maximum Configuration (Cluster)	Up to 2 nodes, either Active/Active or Active/Passive	Up to 4 Active nodes +1 Standby node
Processors	2 x Intel Xeon 4110	2 x Intel Xeon 4114
RAM	64 GB	384 GB
Form Factor	2U	2U
Number of GBe Ports	4	4
Number of 10Gb Ports	2 Optional	2 Optional
Number of FC Ports	12 (16 GB)	4 (16 GB) + 2 Optional
Number of SAS Input Ports	0	0
Number of SAS Output Ports	0	0
Internal storage capacity (usable)	800 GB (0)	800 GB (0)
# drives	2 x 400 GB - RAID 0	2 x 400 GB - RAID 0
Dimensions (H x W x D):	3.40" x 17.44" x 26.80"	3.40" x 17.44" x 26.80"
Weight:	57.54 lbs	57.54 lbs
Temperature / Humidity considerations:	10 - 35°C / 10 - 80%	10 - 35°C / 10 - 80%
Heat output / cooling requirements:	4,100 BTU's/hr	4,100 BTU's/hr
Power supply rating (self switching)	100 - 240v, 50/60hz	100 - 240v, 50/60hz
Power / breaker requirements - US / C	1,100w/110v/12a	1,100w/110v/12a
Power / breaker requirements - Int'l	1,100w/240v/6.5a	1,100w/240v/6.5a

Visit us at DynamicSolutions.com or call **303.754.2088** to speak directly with a solutions architect.



Dynamic Solutions
INTERNATIONAL

UNISYS