



Dynamic Solutions
INTERNATIONAL

"Protecting the World's Information"



iDSI520 Enterprise Series

Experience You Can Trust

Protecting the world's information is our mission. Offering 45+ years of experience in data protection solutions and expertise in both disk and tape technologies, DSI meets the needs of IT professionals worldwide. DSI offers optimized solutions for data backup, recovery and archiving. DSI has award winning designs, patented technologies, superior reliability, first class service and a variety of solutions customized to meet your needs.

Maximize Use of Valuable Resources

The iDSI520 Series Virtual Tape Library offers the most robust data protection for our customers. The iDSI520-EV0 may be paired with any DSI qualified fibre-channel external storage in your environment, allowing expansion into the petabytes of backup capacity.

Protect Your Investment

Data security is imperative when building a backup and disaster recovery solution. DSI utilizes the industry's top standards for at-rest and in-flight encryption to ensure that your data is never exposed to outside threats. The iDSI520 ships standard with in-flight and at-rest encryption so your data is protected every step of the way.

Maximize Your Data Center Efficiency

Data centers worldwide face the challenge of business critical data growing exponentially. The iDSI520-EV0 may be paired with an iDSI520-EVD to insure maximum possible power, management and physical space efficiency.

DSI also offers consulting services to assist with strategic backup and disaster recovery (DR) planning, design and implementation.

Build Your Systems, Your Way

The iDSI520 Series provides scalable, enterprise-class data protection available for any environment.

Component Description for iDSI520

iDSI520-EV0: may be paired with any DSI qualified Fibre-Channel external storage in your environment, allowing expansion into the petabytes of backup capacity.

iDSI520-EVD: The enterprise deduplication module may be paired with certified third-party disk arrays. No physical storage is included with the EVD head node.



See configuration table for details.

THE iDSI520 IS
DESIGNED TO HELP
YOU KEEP PACE
WITH YOUR
RAPIDLY
EXPANDING DATA
FOOTPRINT BY
UTILIZING STATE-
OF-THE-ART
DEDUPLICATION.



Dynamic Solutions International
373 Inverness Parkway
Suite 110
Englewood, CO 80112

Phone 303.754.2080
Fax 303.754.2066
DynamicSolutions.com
IBMsizing@ynamicsolutions.com
IBMsales@ynamicsolutions.com

| |  iDSI520-EV0 |  iDSI520-EVD |
|---|---|---|
| | VTL Node | Deduplication Node |
| End user capacity | Up to 3.8PB | |
| | Enterprise VTL Node | Enterprise Deduplication Node |
| # virtual libraries | 128 | |
| # virtual tape drives | 1,024 | |
| # virtual tape cartridges supported | up to 1,000,000* | |
| Backend physical tape | FC only | |
| Replication (w/ encryption / compression) | Included | |
| SecureTape encryption | Included | |
| Tape consolidation (stacking) | Included | |
| High Availability | Optional | N + 1 Option |
| Data De-duplication | Requires iDSI520 EVD | Yes |
| VTL Agent | Included | Included** |
| Open systems ISV attachment | yes | yes |
| DSI Tracker / DSI Conductor | Optional | n/a |
| Maximum Configuration (Cluster) | Up to 2 nodes, either Active/Active or Active/Passive | Up to 4 Active nodes +1 Standby node |
| Processors | 2 x Intel Xeon 4110 | 2 x Intel Xeon 4114 |
| RAM | 64 GB | 384 GB (768GB option for EVD+) |
| Form Factor | 2U | 2U |
| Number of GBe Ports | 4 | 4 |
| Number of FC Ports | 12 (16 GB) | 4 (16 GB) + 2 OPTIONAL |
| Number of 10Gb Network Ports | 2 Optional | 2 Optional |
| Number of SAS Input Ports | 0 | 0 |
| Number of SAS Output Ports | 0 | 0 |
| Internal storage capacity (usable) | 800 GB (0) | 800 GB (0) |
| # drives | 2 x 400 GB - RAID 0 | 2 x 400 GB - RAID 0 |
| Dimensions (H x W x D): | 3.40" x 17.44" x 26.80" | 3.40" x 17.44" x 26.80" |
| Weight: | 57.54 lbs | 57.54 lbs |
| Temperature / Humidity considerations: | 10 - 35°C / 10 - 80% | 10 - 35°C / 10 - 80% |
| Heat output / cooling requirements: | 4,100 BTU's/hr | 4,100 BTU's/hr |
| Power supply rating (self switching) | 100 - 240v, 50/60hz | 100 - 240v, 50/60hz |
| Power / breaker requirements - US / C | 1,100w/110v/12a | 1,100w/110v/12a |
| Power / breaker requirements - Int'l | 1,100w/240v/6.5a | 1,100w/240v/6.5a |

* Max virtual tapes supported includes local tapes and replicas

** DSI VTL Agent is included on the DSI520-EVD, when the DSI VTL Conductor software is also ordered

Visit us at DynamicSolutions.com or call **303.754.2088** to speak directly with a solutions architect.



Dynamic Solutions
INTERNATIONAL



Ready for
Power Systems Software